



**Water Care 101:** Changes to your swim spa's water chemistry are normal and can happen rapidly based on many factors including usage, water temperature, and water level. Regular testing and adjustments are recommended for a fun and safe swim spa ownership experience. The following guide outlines our recommended steps that you should take to maintain your swim spa's water care. *Don't worry, you'll be a pro in no time!*

**Have These Items Ready:**

- @ease Test Strips
- SpaFrog Jump Start Packet(s)
- Floating Mineral Cartridge (Blue)
- Floating SmartChlor Cartridge (Silver)



**Pro Tip:** When using the FROG @ease system it is required to use @ease test strips!

**\*\*\*Always activate jets when adding water care products, unless noted otherwise\*\*\***

**FRESH FILL (Start Up)**

*Follow these steps during initial filling or refilling after draining.*

1. Fill swim spa with water (use a **Pre-Filter** during the fill cycle for well water). First, remove filter and filter lid/basket. Add water directly to swim spa through the filter compartment. Fill to above all jets and just below pillows/headrests (please refer to your specific model's owner's manual for details).



2. After filling, replace filter components and follow the instructions provided in your owner's manual to turn on your swim spa and begin heating.

3. Add **SpaGuard Stain & Scale Control** (1 oz. per 100 gallons)

*Ideal Range: Adjust with:*

4. Check and balance total alkalinity.

80-120 ppm

**SpaGuard Total Alkalinity Increaser**  
**SpaGuard pH Decreaser**

5. Check and balance pH.

7.2-7.8 ppm

**SpaGuard pH Increaser or pH Decreaser**

6. Check calcium hardness.

Up to 250 ppm

**SpaGuard Calcium Hardness Increaser**  
(not included in start-up kit)


*IF out of range, contact Georgia Spa before adjusting.*

7. Add **SpaFrog Jump Start** packet(s) to the water (one packet per 600 gallons).

8. Remove the **@ease Mineral Cartridge (Blue)** from the box. This cartridge will last 4 months.

9. Attach the **@ease SmartChlor Cartridge (Silver)** to the **@ease Blue Mineral Cartridge (Blue)**. This cartridge will last 2-4 weeks depending on your swim spa size and number of users.

Gallons	Setting
< 1,800	2
1,800-2,200	3
> 2,200	4



10. Attach to railing of swim spa with the tether provided. *Optional rubber tether available as in-store purchase.*

**\*\*\*Leave cover open for a minimum of 20 minutes for off-gassing to prevent damage to cover and pillows\*\*\***



**GEORGIA SPA CO.**

An Employee Owned Company

# Swim Spa Start Up & Maintenance Guidelines @ease Floating Sanitizing System

**\*\*\*Pro Tip: Maintenance frequency may vary based on usage\*\*\***

## PUTTING THE SYSTEM TO WORK:

1. Connect the **@ease Mineral Cartridge (Blue)** to the **@ease SmartChlor Cartridge (Silver)**. Push together until you hear the cartridges click into place.
2. Set the dial on the bottom of the **@ease SmartChlor Cartridge (Silver)** accordingly (see step 9 of Fresh Fill instructions) and toss it into the water.



## WEEKLY SPA CARE:

1. Test and balance your **total alkalinity** and **pH** (refer to steps 4-5 of the Fresh Fill instructions).
2. Maintain a minimum of 0.5 to 1.5 ppm of free chlorine at all times. Using the **@ease test strips**, verify your color is the same or darker for SmartChlor. If it is lighter, your cartridge may need to increase an output setting, or it may be empty and needs to be replaced.
3. If the floating system is "silver side up" it is time to replace the **@ease SmartChlor Cartridge (Silver)**.



**\*\*\*Pro Tip: Do not use Chlorine Concentrate products with the @ease system\*\*\***

## EVERY 30 DAYS:

1. Shock the swim spa with **SpaGuard Spa Shock Oxidizer** when you replace the **@ease SmartChlor Cartridge (Silver)**, or once per month, whichever occurs first.
2. Check your filters. It is recommended to clean your filters every 4 weeks using **SpaGuard Filter Cleaner**. Best results are achieved when the filters are soaked in filter cleaner overnight. Be sure to rinse the filters thoroughly before placing them back into the swim spa. Dirty filters may cause cloudy water, low jet pressure, FLO errors in your swim spa, among other things.



PRO TIP: Having an extra set of filters to rotate at cleaning helps speed up this process.

**FREE Water Testing!** Bring us a sample of your swim spa water, and we'll test it and provide a report of steps to take to adjust your spa water. Showrooms open Monday-Saturday, 10 a.m. - 7 p.m., and Sunday 1-5 p.m. **We recommend having your water tested every 30 days.**

## EVERY 4 MONTHS:

1. If necessary, drain and refill your swim spa (following the Fresh Fill Start Up instructions).
  - Clean your swim spa using **303 Multi-Surface Cleaner**. Do NOT spray entire spa.
  - Spray on a cloth rag and spot clean as needed.
2. Replace the **@ease Mineral Cartridge (Blue)**.

PRO TIP: Sign up for our **Home Auto Ship** Program and when your shipment arrives it's the reminder you'll need to change the Mineral Cartridge.



*Let us help you with water care!*

Hot tubs are made for relaxation and enjoyment. With our **EZ Valet Service** we will take care of the details so that you can take care of the enjoyment. Select from a single-visit drain and clean service or choose a weekly, bi-weekly or monthly valet plan.



Scan to see our EZ Valet Plans